



# EUROSTYLE ORGANIC WATERPROOF O.R.C.A. BOARD FLOORING

## SPEC SHEET

<b>Category</b>	Waterproof O.R.C.A. Board Flooring
<b>Dimensions</b>	Wood Design - 5/16" or 1/2" (thickness) x 7 1/2" (width) x 50 9/16" (length) Tile Design - 5/16" (thickness) x 12 7/8" (width) x 25" (length)
<b>Radiant heat</b>	Radiant heat compliance (water pipes embedded in thermo mass only)
<b>Installation</b>	By floating
<b>Warranty</b>	30 year residential warranty 5 year commercial warranty

 ANTI BACTERIAL COMFORT	 V4 GROOVE	 1CLIC 2GO PURE+	 MICROSCRATCH PROTECT	 ANTI-STATIC
 PET PROOF	 LIGHT-RESISTANT	 ECO FRIENDLY	 ÉMISSIONS DANS L'AIR INTÉRIEUR A+	
 23	EN 13329	 33	 CARB P2 & U.S. EPA TSCA Title VI compliant conforme au titre VI de la TSCA	
 C <sub>fl</sub> -s1		 E1 HCHO	 DS	 DL PCP



EN 14041:2004/AC:2006; C<sub>fl</sub>-s1; E1; DS; PCP < 5ppm; 0,08 W/(m·K),  
Bodenbeläge für die Verwendung in Gebäuden,  
DoP: LW0012017/NB 0766; NB 0767  
Kronoflooring GmbH, Mühlbacher Str.1, 01561 Lampertswalde, Germany  
DoP: www.floor-installation.com